



KOYO BEARING LTD



130 mm x 230 mm x 40 mm skf 7226 bcbm bearing

Bearing No. 7226 bcbm

7226 bcbm Bearing 2D drawings and 3D CAD models

Category	Angular Contact Ball Bearings
Inventory	2.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	6.77
EAN	7316577745095
Product Group	B00308
Enclosure	Open
Flush Ground	Yes
Rolling Element	Ball Bearing
Number of Rows of Balls	Single Row
Precision Class	ABEC 3 ISO P6
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Brass
Contact Angle	40 Degree
Internal Clearance	CB
Number of Bearings	1 (Single)
Mounting Arrangement	Universal
Inch - Metric	Metric
Long Description	130MM Bore; 230MM Outside Diameter; 40MM Width; Open; Yes Flush Ground; Ball Bearing; Single Row of Balls; ABEC 3 ISO P6; No Filling Slot; No Snap



KOYO BEARING LTD

	Ring
Other Features	Normal Axial Internal Clearance
Category	Angular Contact Ball Bearing
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	7226 BCBM
Weight / LBS	14.909
B	1.575 Inch 40 Millimeter
d	5.118 Inch 130 Millimeter
D	9.055 Inch 230 Millimeter
bore diameter:	130 mm
radial static load capacity:	193 kN
outside diameter:	230 mm
cage material:	Brass
overall width:	40 mm
outer ring width:	40 mm
contact angle:	40 °
maximum rpm:	3400 RPM
row type & fill slot:	Single-Row Non-Fill Slot
finish/coating:	Uncoated
internal clearance:	C0
precision rating:	ABEC 3 (ISO Class 6)
closure type:	Open
fillet radius:	2.5 mm
radial dynamic load capacity:	186 kN
series:	72
d	130 mm



KOYO BEARING LTD

D	230 mm
B	40 mm
d ₁	168.9 mm
d ₂	149.57 mm
D ₁	192.55 mm
a	96 mm
r _{1,2} min.	3 mm
r _{3,4} min.	1.1 mm
d _a min.	144 mm
D _a max.	216 mm
D _b max.	222 mm
r _a max.	2.5 mm
r _b max.	1 mm
Basic dynamic load rating C	186 kN
Basic static load rating C ₀	193 kN
Fatigue load limit P _u	6.1 kN
Reference speed	3400 r/min
Limiting speed	3800 r/min
Calculation factor A	0.605
Calculation factor k _r	0.08
Calculation factor e	1.14
Calculation factor X	0.35
Calculation factor Y ₀	0.26
Calculation factor Y ₂	0.57
Calculation factor X	0.57
Calculation factor Y ₀	0.52
Calculation factor Y ₁	0.55
Calculation factor Y ₂	0.93
Mass bearing	6.95 kg